

**IDEAL FOR
CONTINUOUS OPERATION**

PREBENA®

www.prebena.com

Pneumatic construction nailer 3GP-CNH50 for coilnails type CNH from 25 - 50 mm (1" - 2")



OPTIWEAR- TECHNOLOGY

Highest performance, ideal energy utilization and long life

- Optimized wearing parts
- Long service life
- Easy maintenance
- Smooth-running trigger system
- Low noise and vibration level
- Fast fire sequence
- Powerful
- Low air consumption
- No recoil



Technical details:

Weight: 1,97 kg (4.343 lb.)

Operating pressure: 5 - 8 bar (71 - 114 psi.)

Air requirement: 0,92 l/nail (0.202 gal./nail)

Measurements: H 340 x W 138 x L 285 mm
(H 13.39 x W 5.0 x L 11.22 in.)

Applications:

Roof- and wall claddings out of aluminium, stainless steel or titanium zinc, valley boards and metal sheet fixing on wood

- Ideal handling for multi-purpose usage
- Special device for optimal nailing
- Depth adjustment without tools
- Low weight for optimal operating comfort
- User-friendly trigger
- Practical magazine lock
- High-quality coil magazine
- Single shot
- Ergonomic rubbered handle grip
- Adjustable exhaust



PREBENA Wilfried Bornemann GmbH & Co. KG

Seestraße 20 - 26 • 63679 Schotten • Germany

Telefon: +49 6044 96 01-0 • Fax: +49 6044 96 01-820 • info@prebena.com