

IDEAL FOR CONTINUOUS OPERATION

PREBENA®

www.prebena.de

Pneumatic Stapler 3GP-H40 for staples type H from 15 - 40 mm (19/32" - 1-9/16")

OPTIWEAR- TECHNOLOGY

Highest performance, ideal energy utilization and long life

- Optimized wearing parts
- Long service life
- Easy maintenance
- Smooth-running trigger system
- Low noise and vibration level
- Fast fire sequence
- Low air consumption
- No recoil



1,0 x 1,25 mm
(0.039 x 0.049 in.)

8,6 mm
(0.339 in.)

15 (19/32")
21 (5/8")
25 (1")
30 (1-3/16")
35 (1-3/8")
40 (1-9/16")

Type H

Technical details:

Weight: 1,83 kg (4.03 lb.)

Operating pressure: approx. 5 - 8 bar (72 - 116 psi.)

Air requirement: approx. 1,28 l (0.282 gal.) / staple

Measurement LxWxH: 295 x 70 x 265 mm

(11.61 x 2.76 x 10.43 in.)

Applications:

Prefabricated constructions, wooden truss, packing, plasterboard, framework, furniture manufacturing, etc.

- Ideal handling for multi-purpose usage
- Low weight
- User-friendly trigger system
- Practical magazine lock
- High quality bottom loading magazine for fast reloading
- Bump fire
- Depth control
- Belt hook
- Ergonomical anti-slip handle
- Exhaust silencer
- in a plastic case

PREBENA Wilfried Bornemann GmbH & Co. KG

Seestraße 20 - 26 • D-63679 Schotten

Phone: 0049 6044 / 9601 - 0 • Fax: 0049 6044 / 9601 - 820 • info@prebena.com