

# IDEAL FOR CONTINUOUS OPERATION

# PREBENA®

www.prebena.de

## Pneumatic Stapler 3GP-Z40 for staples type Z from 16 - 40 mm (5/8" - 1-9/16")



1,4 x 1,6 mm  
(0.055 x 0.00.063 in.)

11,2 mm  
(0.441 in.)

16 (5/8")  
25 (1")  
28 (1-1/8")  
30 (1-3/16")  
32 (1-1/4")  
35 (1-3/8")  
38 (1-1/2")  
40 (1-9/16")

Type Z

## OPTIWEAR- TECHNOLOGY

Highest performance, ideal energy utilization and long life

- Optimized wearing parts
- Long service life
- Easy maintenance
- Smooth-running trigger system
- Low noise and vibration level
- Fast fire sequence
- Low air consumption
- No recoil



### Technical details:

Weight: 1,83 kg (4.03 lb.)

Operating pressure: approx. 5 - 8 bar (72 - 116 psi.)

Air requirement: approx. 1,28 l (0.282 gal.) / staple

Measurement LxWxH: 295 x 70 x 265 mm

(11.61 x 2.76 x 10.43 in.)

### Applications:

Fermacell, plasterboard, boxes, corrugated cardboards, cedar and shake shingles, chipboards, packaging, substructures, saving formwork, cardboard pallets, prefab construction, etc.

- Ideal handling for multi-purpose usage
- Low weight
- User-friendly trigger system
- Practical magazine lock
- High quality bottom loading magazine for fast reloading
- Bump fire
- Depth control
- Belt hook
- Ergonomical anti-slip handle
- Exhaust silencer
- in a plastic case

PREBENA Wilfried Bornemann GmbH & Co. KG

Seestraße 20 - 26 • D-63679 Schotten

Phone: 0049 6044 / 9601-0 • Fax: 0049 6044 / 9601-820 • info@prebena.com